Qty: _____*AutoCad available on KCL

SELF-CONTAINED CUBER WITH BUILT-IN STORAGE BIN

KM-201B_H 3/09 Item # 13238


CUBER DIMENSIONS W x D x H

KM-201B_H24 × 28 × 39*



KM-201BAH

Air-Cooled Shown



- Built-in 80 lbs. ice storage
- Individual crescent cube
- Durable stainless steel exterior
- CycleSaver® Design CYCLESAVE



- EverCheck® alert system
- Stainless steel evaporator
- Removable air filter
- Complies with California Energy Commission guidelines (CEC)
- R-404A Refrigerant
- * The KM-201BAH is ENERGY STAR certified.







Warranty

Valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in other countries.

Three Year - Parts & Labor on entire machine.

Five Year - Parts & Labor on: Evaporator.

Five Year - Parts on: Compressor, air-cooled condenser coil.





KM-201B_H SELF-CONTAINED CUBER WITH BUILT-IN STORAGE BIN

DIMENSIONS

W x D x H

KM-201B_H

24 x 28 x 39*

*with 6" legs

Air-cooled

AIR-COOLED


Water Temp° F.		50°	70°	90°
Air Temp° F.	70°	201	190	176
	80°	193	177	162
	90°	190	165	150


UTILITY CONSUMPTION


Model Number		duction Cycle Cubes	KWH per 100 LBS. 90/70	Potable Water Gal. per 100 lbs.	Condenser Water Gal. per 100 lbs.
KM-201BAH	4	182	7.5	22.0	N/A

SPECIFICATIONS

Model Number	Condenser	Amperage	Shipping Weight
KM-201BAH	Air-Cooled	6.1	165 lbs.







SIDE VIEW

BACK VIEW / AIR-COOLED UNIT

ELECTRICAL & PLUMBING/KM-201BAH

- 115V/60/1
- 15 amp Max Fuse/HACR Breaker Size
- 3/8" OD copper or equivalent independent potable water supply
- 3/4" FPT independent drain connection
- 1/2" FPT water inlet









© HOSHIZAKI AMERICA, INC.

OPERATING LIMITS

- Ambient Temp Range
- Water Temp Range
- Water Pressure • Voltage Range
- 45 90°F

45 - 100°F

10 - 113psig 104 - 127V

SERVICE

- Panels easily removed and all components accessible for service.
- Removable/cleanable air filters

